

CHAPTER 7

Approval and Acceptance of an Aircraft Operating Manual (AOM) Part B

1.0 PURPOSE

This Chapter provides guidance to Flight Operations Inspectors (FOIs) and the Airworthiness Inspectors (AWIs) on the evaluation and approval of an Aircraft Operating Manual (AOM) Part B.

2.0 REFERENCE

2.1 Regulation 9.3.1.4 and 8.2.1.6 of the Nigeria Civil Aviation Regulations.

2.2 Aircraft Operating Manual (applicable)

2.3 CHECKLISTS: [CL: O-OPS007](#)

3.0 GENERAL

3.1 Part 9 of the Nigeria Civil Aviation Regulations require the operator to submit an AOM containing the normal, abnormal and emergency procedures relating to the operation of the aircraft to the Authority for approval. An approved AOM is an approved manual that needs to be carried aboard an aircraft. Inspectors must evaluate an operator's AOM using the guidance that follows.

3.2 **Definition.** Aircraft Operating Manual (AOM) is a Manual, acceptable to the State of the Operator, containing normal, abnormal and emergency procedures, checklists, limitations and performance information, details of the aircraft systems, and other materials relevant to the operations of the aircraft.

3.3 **Identification as an Approved Manual.** Inspectors must ensure that an AOM and the Aircraft Flight Manual (AFM) are clearly marked as approved manuals for a specific operator. Sections of an AOM which contain approved information must also be clearly identified.

3.4 **Approved Sections of an AOM.** Inspectors must ensure that the approved sections of an AOM contain all of the information that is required by the flight crew to operate the aircraft. Inspectors should evaluate the approved sections of an AOM for the following:

3.4.1 The procedures section of an AOM must contain all procedures required by the Aircraft Flight Manual and for each operation the operator conducts. As a minimum, the operator must include sufficient detail to allow a trained flight crewmember to safely and effectively operate the aircraft. The Procedures Section of the manual may be divided into subsections such as normal, abnormal, and emergency procedures;

3.4.2 The operator's performance data in an AOM must contain the data from the AFM and instructions on how to use that data. Operators may assign the responsibility for performing takeoff and landing data computations to flight crew or ground personnel. The flight crew must have access to adequate data

in the cockpit, (including information for the specific airport and runway to be used) to perform the computations for which they are responsible. When takeoff and landing data is presented in tabular format for specific runways, it is often referred to as an airport analysis. Performance data may be published under separate cover and be given titles such as performance manual or airport analysis. When performance data is published under separate cover, it must be identified as a portion of the AOM. Takeoff and landing performance data may be stored in an on board or ground based computer;

- 3.4.3 The Limitations Section of an AOM must be clearly identified as being approved. The Limitations Section of an AOM must contain each limitation, which is contained in the AFM.

3.5 Accepted Sections of an AOM. Accepted sections of an AOM may contain supplementary information such as aircraft and systems descriptions, an expanded explanation of procedures, special policies and procedures, and other selected topics pertinent to operation of the aircraft type. The accepted sections of an AOM must conform to the regulations and safe operating practices but do not need to conform to corresponding sections of the AFM, either in format or content. Inspectors should ensure that the AOM developed by or for the operator contains sufficient explanation and guidance for the use by flight crew in the safe operation of the particular aircraft type. Background information or information that is not specific to the operation of the particular aircraft should be placed in a section of the Operations Manual, rather than in a supplementary section of the AOM.

3.6 Review to AFM/RFM Changes. The Inspector shall ensure that the AOM is developed and revised using the most current revision of the AFM/RFM. These changes shall be in compliance with the changes made mandatory by the State of Registry/State of Design. Changes in the operator's operations specifications should be accompanied by a review of applicable sections of the operator's manual.

4.0 AIRCRAFT SYSTEMS DESCRIPTION

Operators must provide crew members with a systems description of an aircraft's systems and components that contains sufficient detail to allow flight crew members to adequately understand and perform all procedures in the approved manual. AFMs and AOMs may or may not contain a systems description section. The aircraft systems description section of a manual is "accepted" as opposed to "approved." Operators may choose to place the systems description information in an accepted section of an AOM or in a section of the Operations Manual such as the Training Manual Section.

5.0 PROCEDURES

5.1 Inspectors should not construe procedures published in an AFM to be the only or best means of accomplishing a specific objective. Because AFM procedures are formulated primarily for aircraft certification purposes, Inspectors should encourage operators to develop procedures appropriate to revenue operations for inclusion in an AOM.

5.2 Procedures incorporated in an AOM should be tailored by the operator to accommodate the operator's type of operation, fleet standardisation objectives, and cockpit management objectives. As an

operator's operations become more complex, it is progressively more important to include detailed guidance in his AOM, which is specifically tailored to the operator's operations.

- 5.3** Aircraft which have been modified by Supplemental Type Certificate (STC) may require different procedures than unmodified aircraft. FOI's must co-ordinate approval of procedures with Airworthiness Inspector's (AWI's) to ensure modifications are accounted for in the operator's procedures.
- 5.4** Procedural information included in an AOM must be presented in a step-by-step format. A procedural step in an AFM procedure must be included in the equivalent AOM procedure, unless the inspector approves the deletion through the process described in subparagraph I that follows.
- 5.5** Operators are responsible for developing effective Standard Operating Procedures (SOP's). The development process for standard operating procedures consists of the operator or other qualified party (such as the manufacturer) conducting a painstaking task analysis of the man machine environment relationship. Although this analysis is time consuming and expensive, it is necessary to meet the required level of safety in air transport operations. Operators shall confirm with the manufacturers recommendation in the development of Standard Operating Procedures.
- 5.6** Inspectors should ensure that operators standardise their operating procedures both within and across aircraft types to the greatest extent possible. Inspectors should make operators aware of the following information concerning procedures for standardisation:
- 5.6.1** Standardised procedures promote understanding and effective communications between crewmembers. Research has shown that standardised procedures and effective communications are significant factors in reducing error in the cockpit and in enhancing safety;
- 5.6.2** Crewmembers of most large operators operate numerous different aircraft during their career. Standardised procedures enhance a crew members transfer of learning and minimise negative transfer when the crew member transitions from one aircraft to another; and
- 5.6.3** A complete standardisation of procedures is not possible when there are significant differences between "manufacturer's" and "installed" equipment, but a high degree of standardization can still be achieved. For example, the flight procedures for: engine failure after V1, engine fire after V1, and a missed approach with an engine out, can be designed to be identical. Each procedure might include the aircraft climbing at a reference speed to an identical clean up height, then accelerating, then retracting the flaps, and then continuing the climb at specified engine-out climb speed. The reference speeds might vary depending on the aircraft mass, but the procedure could otherwise be identical. If the operator designed these procedures carefully, they could be used on all aircraft in the operator's fleet.
- 5.7** Inspectors may approve combined procedural steps. For example, an AFM or RFM procedure specifies a two-step procedure such as the following: Step 1 - Smoke Goggles On, and Step 2 - Oxygen (O2) Mask On. The inspector could approve a one-step procedure such as the following: Step 1. Smoke Goggles and O2 Mask on. If there is a specific reason, however, for not combining the steps, the inspector must not approve such combinations. For instance, if in the previous example, for some reason the smoke goggle has to be put in place before the O2 mask can be put into place, the two-step procedure should be retained.

- 5.8** Inspectors may approve combined procedural steps. For example, an AFM or RFM procedure specifies a two-step procedure such as the following: Step 1 - Smoke Goggles On, and Step 2 - Oxygen (O2) Mask On. The inspector could approve a one-step procedure such as the following: Step 1. Smoke Goggles and O2 Mask on. If there is a specific reason, however, for not combining the steps, the inspector must not approve such combinations. For instance, if in the previous example, for some reason the smoke goggle has to be put in place before the O2 mask can be put into place, the two-step procedure should be retained.
- 5.9** Inspectors may approve an arrangement of procedural steps in a different sequence from the sequence in the AFM. The operator must demonstrate to the Inspectors satisfaction that the change in sequence is safe and effective through validation testing. The inspector shall ensure adverse effects are not introduced. For example, with many aircraft the flaps are required to be extended or the trim to be set to specific settings before an adequate control check can be accomplished. If this sequence is reversed, the control check is invalid.
- 5.10** Inspectors may approve the combination of similar procedures into a single procedure. For example, it may be desirable for an operator to combine engine fire, engine failure, and severe engine damage procedures into a single procedure. Inspectors may approve the resulting procedure when validation testing demonstrate that the procedure is clear, easy to use, and retains the safeguards of the individual procedures it replaces on the other hand if the combined procedure results in a complex and potentially error prone procedure, the inspector shall not approve it.
- 5.11** The inspector shall require the operator to present evidence that newly developed procedures are effective. This may be done by analysis, documentation, or validation tests. Tests may be conducted by the manufacturer, the operator, or another competent party (such as a contractor). The Flight Operations Inspector qualified in the aircraft type must evaluate the effectiveness of such tests.
- 5.11 Normal Procedures**
- 5.11.1** The normal procedures section of an AOM must contain procedures for each normal operation that flight crew members are required to perform. Each normal procedure should be amplified by the operator with sufficient instruction to ensure that the procedure is properly accomplished. Inspectors must ensure that this instruction is thorough enough to provide the least experienced flight crewmember with sufficient information to perform the procedures.
- 5.11.2** Many operators include normal operating checklists and an explanation of how to accomplish each step of the checklists in the normal Procedures Section of the AOM. This is an acceptable practice; however, it is important to understand that an explanation of how to perform the normal checklist is not the only material required in the normal Procedures Section of an AOM. Guidance for operational procedures for which there are no checklists (such as the takeoff procedure) must also be addressed. Procedures for crew co-ordination and for the use of checklists must be included. The Procedures Section of an AOM must contain clearly specified crew duties. For example, the Procedures Section should contain a specific assignment for the crewmember who is responsible for setting power and maintaining directional control when the co-pilot is conducting a takeoff.

5.11.3 Where an AFM or RFM does not contain normal procedures for specific operations, inspectors may require the Operator to develop and publish normal procedures in the AOM when the procedures are necessary to ensure an adequate level of safety. Instrument approach procedures, adverse weather operations, long range navigation, and special procedures for CAT II and CAT III operations are all examples of required normal procedures which may not be in an AFM or RFM.

5.11.4 Operators may need to develop extensive procedures for operating computer-based systems in the cockpit. A description of computer displays and controls does not normally provide a crew member with adequate information to operate such systems. Procedures for computer operations should be keyed to menus and display prompts. Procedures should be written in an interactive format rather than as a rote listing of keystrokes.

5.12 Manoeuvres and Procedures Document

5.12.1 Regulations require that operators publish "detailed descriptions or pictorial displays of the approved normal, abnormal, and emergency manoeuvres, procedures and functions that will be performed during each flight training phase or flight check, indicating those manoeuvres, procedures and functions that are to be performed during the in-flight portions of flight training and flight checks". Operators must obtain approval of the manoeuvres and procedures descriptions before they are published.

5.12.2 Before approving the operator's "manoeuvres and procedures document," Inspectors shall ensure that it contains the tolerances, which must be maintained in training and checking. Inspectors shall ensure that the operator's standards are appropriate for the aircraft being flown and for the operation being conducted

5.13 Abnormal and Emergency Procedures

5.13.1 Abnormal and emergency procedures in an AFM are usually presented in more detail than normal procedures. The steps and the order of steps in these procedures are often critical. Inspectors must exercise caution in approving the modification of abnormal and emergency procedures. The effects of most procedural steps on the airworthiness of the aircraft are obvious but the effects of some are not. For example, it may be necessary to depressurize a hydraulic system to successfully perform a manual landing gear extension. Deleting a step or a change in the sequence of steps of such a procedure could make the procedure ineffective. There have been instances in which operators have erroneously proposed modifying an AFM procedure, and Inspectors have unintentionally approved the modification, which invalidated the certification basis of the aircraft. Inspectors should use the guidance that follows when evaluating an operator's abnormal or emergency procedures in AFMs or AOMs.

5.13.2 When an operator proposes to modify an abnormal or emergency procedure, the operator must show that the modified procedure does not adversely affect the airworthiness of the aircraft. The operator may establish the safety and effectiveness of proposed procedures by corresponding with the manufacturers and by analysis, documentation, or validation tests.

5.13.3 Inspectors shall contact the applicable appropriate authority and obtain concurrence before approving deletion of an item or the rearrangement of items on these checklists. Appropriate authority concurrence may be expressed informally (by telephone). Appropriate authority concurrence is not required if the operator provides evidence that the appropriate authority has already concurred with the identical procedure for another party (such as another operator or manufacturer).

5.14 Immediate Actions

5.14.1 An immediate action is an action that must be accomplished so expeditiously (in order to avoid or stabilize a hazardous situation) that time is not available for a crewmember to refer to a manual or checklist. Crewmembers must be so familiar with these actions that they can perform them correctly and reliably from memory. Inspectors must ensure that immediate action situations are included in an operator's AFM or AOM, as appropriate. Situations that require immediate action include, but are not limited to the following:

- a) Imminent threat of crew member incapacitation;
- b) Imminent threat of loss of aircraft control;
- c) Imminent threat of destruction of a system or component which makes continued safety of the flight and subsequent landing improbable.

5.14.2 Under these criteria, a flight crew donning oxygen masks in response to a depressurisation or turning off the fuel and ignition in case of a hot start are situations requiring mandatory immediate action items. The loss of thrust on a jet engine during cruise, however, would not normally require an immediate action item according to these criteria.

5.14.3 Inspectors must ensure that immediate action items are explicitly identified as such in an operator's AOM. It is not acceptable for immediate action items to be hidden (not specifically identified as an immediate action) in procedures or checklists.

5.14.4 Certain situations that either require or appear to require immediate action have proven to be a stimulus for generating incorrect and inappropriate flight crew actions. Therefore, immediate action items must be strictly limited to only those actions necessary to stabilise the situation. Inspectors must ensure that all remaining actions are accomplished by "challenge do verify" (CDV) checklists. CDV checklists have checklist items that require confirmation from a second crewmember before the step may be taken.

5.14.5 Inspectors may approve an operator's proposal to replace immediate action items in an AFM procedure with challenge do verify (CDV) checklist procedures in an AOM, provided the operator shows compliance with the criteria in this paragraph and also demonstrates an equivalent level of safety through validation tests.

5.15 Mandatory Confirmation Items

- 5.15.1 There are certain critical procedural steps that must be confirmed by a second crewmember before the step may be taken. Inspectors must ensure that an operator's procedures, which contain such critical procedural actions, clearly identify the critical actions and the crewmember that is responsible for giving the confirmation.
- 5.15.2 The types of procedural actions that require this confirmation include the following:
- Actions resulting in the shutting down of an engine;
 - Actions resulting in the deactivation of flight controls;
 - Actions that if performed incorrectly, in the wrong sequence, or at the wrong time would produce a catastrophic result, even if the incorrect action is not highly likely;
 - Actions where past experience or analysis has shown that there is a high probability for error or incorrect action and which creates a hazardous situation.

5.16 Crew Member Responsibilities

- 5.16.1 The AOM must clearly define the various crew member responsibilities. Inspectors should use the following guidance when ensuring that the operator clearly states policy and guidance for cockpit management in the AFM or AOM, as applicable.
- 5.16.2 **PIC Responsibilities.** The operator's policy and guidance should make it clear that the PIC's primary responsibility is to manage the actions of the crew and the conduct of the flight. While the PIC may delegate the management of the flight and manipulation of the controls to the co-pilot, the AOM must not indicate that the PIC can delegate the responsibility for safe conduct of the flight.
- 5.16.3 **Responsibilities of Flight Crew members Not in Command.** The operator's Operations Manual should contain policy and guidance to those flight crew members not in command, as to their responsibilities to the PIC and their responsibilities for the safe conduct of the flight.
- 5.16.4 **Co-pilot Responsibilities.** The AOM must contain guidance for the PIC concerning the conditions and circumstances in which a co-pilot may operate the aircraft. The operator's policies must delineate the limits of authority delegated to the co-pilot when the co-pilot is the pilot flying (PF). The operator's policies should address crew management in critical situations. For example, there may be certain situations in which the co-pilot should be the pilot flying (PF) so that the PIC can concentrate on managing those situations, particularly ensuring that required actions and appropriate checklists are properly accomplished. Procedures for transfer of control must be clearly addressed in the AOM. PM stands for Pilot Monitoring.
- 5.16.5 **Communications.** In general, proper cockpit management requires effective communication and co-operative action between crew members, which form consecutive, closed loops. An example of this interaction is in the illustration that follows.

of an AOM must contain every limitation from the AFM. Operators may add limitations to AOMs which were not in an AFM. One method of accomplishing this is for the operator to express all operator-imposed limitations as policy statements in applicable procedures. When the operator chooses to blend AFM and operator-imposed limitations in the limitations section of an AOM, the inspector must ensure that the operator used a method for clearly distinguishing each AFM limitation from the operator-imposed limitations.

- 5.18.3 The operator is responsible for informing crew members of all AFM operating limitations. Crewmembers are responsible for observing all AFM limitations. The inspector must ensure that the AOM contains a statement that crewmembers are responsible for being aware of and for observing all limitations.

6.0 RESULTS

- 6.1 After the review of the AOM is completed the assigned inspector will notify the operator in writing accompanied by a completed general activity form with the listed discrepancies-

- 6.1.1 If discrepancies are found:

- a) The notice will be accompanied by a completed prescribed form listing specific discrepancies found and recommendations, outlining what will be required to correct the discrepancies;
- b) Treat re-submissions as revisions;

- 6.1.2 When the inspector is satisfied that the AOM meets all requirements:

- a) Circle "YES" in the section for recommendation on the Activity checklist and advise the CPM;
- b) Return the original approved AOM to the operator accompanied by a letter of approval;
- c) Maintain a copy of the AOM at the Authority;

These same procedures will be followed when a revision to the original or approved AOM is received from the operator.